

THULI TOUR CONVERSION BASE



Two tables in one! Ingeniously converts the Tour Portable Table to an Elevation Table in minutes. Simply fold the legs inside and mount your portable table to the Conversion Base using four hand turn knobs. Detaches quickly when the need for a portable table arises. Retrofits to all Tours since 1990.

\$1800 Metal Conversion Base
2400 Oak Conversion Base
25 Cord Cover

CONVERSION BASE SPECIFICATIONS

- Length:** Base: 53" (135 cm)
With Tour attached: 66" (168 cm), extends to 72" (188 cm)
- Width:** Base at widest point: 19" (48 cm)
With Tour attached: 20" (51 cm)
- Height:** Metal Lift with Tour attached: Choose 19" - 29" (48 - 74 cm)
or 21" - 31" (53 - 79 cm)
Oak Encased Lift with Tour attached: 19" - 29" (48 - 74 cm)
- Conversion Time:** Less than 5 minutes to attach or detach Tour Portable Table to Conversion Base
- Base Construction:** Grey powder-coated Metal or Metal Encased in Oak
- Weight:** Metal: 100 lbs (46 kgs), Oak: 115 lbs (52 kgs)
With Tour attached: 150 - 171 lbs (68 - 78 kgs)
- Shipping:** Common Carrier
- Box size:** 56" x 26" x 16" (143 x 66 x 41 cm)
- Shipping Weight:** 120 - 135 lbs (54 - 62 kgs) actual weight
230 - 245 lbs (105 - 112 kgs) dimensional weight for shipping cost

ELECTRIC LIFT MOTOR SPECIFICATIONS

- Weight capacity:** 900 lbs (409 kgs)
- Vertical Travel:** 0 - 10" (0 - 25 cm), quiet & smooth
- Vertical Speed:** Approx. 1" (2.5 cm) per second
- Construction:** Swiss-engineered & manufactured, anodized aluminum telescoping columns, worm-gear integrated linear drive
- Electrical:** 10 volt/10 amp (230 volt available)
- Switch:** Electropneumatic foot switch (black)
- Electrical Cord:** Hospital-grade cordset (grey) with ground, 10 ft (3 m)
- Cord Cover:** Grey, 6 ft (1.8 m) long, optional
- Warranty:** 1 year



THULI TABLES, INC.

4160 Rohowetz Rd, Dodgeville, WI 53533 • 800.458.4854 • 608.935.9300 • Fax: 608.935.9192 • www.thuli.com